


Miniature With Screw Terminals

1135T Series




Applications

- Ideal for limited space applications
- Hermetically sealed switches resist corrosion and build up
- Ideal for use in dusty areas
- Cover, spacer, screws included

General Specifications

Enclosure	ABS Plastic
Temperature Range	-40°F to 150°F (-40°C to 65°C)
Environmental	Hermetically Sealed Reed Switch
NEMA Rating	1
Protection Class	IP 62
Response Time	1 msec max.
Life Cycles	100,000 Under Full Load, 10,000,000 Under Dry Circuit
Connection	#6 screw terminal
Color Choices	Natural (N), Mahogany (M)



Order Information		Electrical Specifications				
Part Number	Contact ¹ Configuration	Load Rating (AC/DC)	Switching Voltage (AC/DC)	Switching Current (AC/DC)	Contact Resistance	Sense Range ² Nominal
1135T-N	N.O.	7.5W/VA	100V	0.5A	0.2 Ohms	0.6" (1.6cm)
1136T-M	N.C.	3W/VA	30V	0.25A	0.2 Ohms	0.6" (1.6cm)

Warning— Each electrical rating is an individual maximum and cannot be exceeded!

¹ Configuration with actuator away from the switch

² Proximity of ferrous materials usually reduces sense range — typically by 50%. The shape and type of material cause a wide diversity of effects.

Testing is required to determine actual sense range for specific applications. As measured on a nonferrous surface.

Gap distances are nominal make distance ± 20%. Gap Specifications are for switch to make. Break distance is approximately 1.1 to 1.5 times make.