

5KV CLASS DISTRIBUTION TRANSFORMERS

Hammond medium voltage transformers are designed for stepping down incoming higher voltage power to utilize voltages for commercial, institutional or industrial applications. The standard NEMA 3R ventilated construction is suitable for indoor or outdoor applications.

ALUMINUM & COPPER WOUND STANDARD SPECIFICATIONS



SINGLE PHASE

THREE PHASE

	15 to 333 kVA	15 to 750 kVA
UL Listed	File: E147879	File: E147879
CSA Certified	File: LR3902	File: LR3902
Frequency	60 Hz	60 Hz
Insulation System	220°C (150°C rise) 200°C (130°C rise) on some copper units (optional 115°C and 80°C rise available)	220°C (150°C rise) 200°C (130°C rise) on some copper units (optional 115°C and 80°C rise available)
Enclosure Type	Heavy Duty Ventilated NEMA Type 3R (optional NEMA 4, 4X and 12 available)	Heavy Duty Ventilated NEMA Type 3R (optional NEMA 4, 4X and 12 available)
Enclosure Finish	ANSI 61 Grey, UL50	ANSI 61 Grey, UL50
Standard Primary Taps	Refer to wiring diagrams for details.	Refer to wiring diagrams for details.
Termination	Front accessible separate high and low voltage terminals; connectors suitable for aluminum and copper are provided for easy cable installation.	Front accessible separate high and low voltage terminals; connectors suitable for aluminum and copper are provided for easy cable installation.
Conduit Knock-Outs	Standard on most units up to 100 kVA.	Standard on units up to 150 kVA.
Impedance	Typically 2 to 5%.	Typically 3 to 6%.
Mounting	Standard floor, wall or ceiling mounting available on units up to 50 kVA. Floor mounting only on units 75 kVA and above.	Standard floor, wall or ceiling mounting available on units up to 45 kVA. Floor mounting only on units 75 kVA and above.

Other voltages not listed in this section are available upon request for both aluminum and copper wound units. Please contact customer service for details, price and availability.

ALUMINUM WOUND, SINGLE PHASE, NEMA 3R STYLE ENCLOSURE

2400 Delta Primary Volts

120/240 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVF015RE	NH6	23.90	25.00	28.75	200	F or W *	SCD 6
25	MVF025RE	NH6	23.90	25.00	28.75	280	F or W *	SCD 6
37.5	MVF037RE	NH6	23.90	25.00	28.75	300	F or W *	SCD 6
50	MVF050RE	NH3	26.00	25.00	38.00	380	F or W *	SCD 6
75	MVF075RE	NH3	26.00	25.00	38.00	500	F	SCD 6
100	MVF100RE	NH4	32.00	29.50	41.00	620	F	SCD 6
150	MVF150RE	NJ4	32.00	32.50	50.00	800	F	SCD 6
167	MVF167RE	NJ4	32.00	32.50	50.00	1000	F	SCD 6
250	MVF250RE	NJ4	32.00	32.50	50.00	1300	F	SCD 6
333	MVF333RE	NJ2	48.50	38.40	59.00	1650	F	SCD 6

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

4160 Delta Primary Volts

120/240 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVF015SE	NH6	23.90	25.00	28.75	200	F or W *	SCD 6
25	MVF025SE	NH6	23.90	25.00	28.75	280	F or W *	SCD 6
37.5	MVF037SE	NH6	23.90	25.00	28.75	300	F or W *	SCD 6
50	MVF050SE	NH3	26.00	25.00	38.00	380	F or W *	SCD 6
75	MVF075SE	NH3	26.00	25.00	38.00	500	F	SCD 6
100	MVF100SE	NH4	32.00	29.50	41.00	620	F	SCD 6
150	MVF150SE	NJ4	32.00	32.50	50.00	800	F	SCD 6
167	MVF167SE	NJ4	32.00	32.50	50.00	1000	F	SCD 6
250	MVF250SE	NJ4	32.00	32.50	50.00	1300	F	SCD 6
333	MVF333SE	NJ2	48.50	38.40	59.00	1650	F	SCD 6

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.



COPPER WOUND, SINGLE PHASE, NEMA 3R STYLE ENCLOSURE

2400 Delta Primary Volts

120/240 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVF015RECN	NH6	23.90	25.00	28.75	220	F or W *	SCD 6
25	MVF025RECN	NH6	23.90	25.00	28.75	300	F or W *	SCD 6
37.5	MVF037RECN	NH6	23.90	25.00	28.75	330	F or W *	SCD 6
50	MVF050RECN	NH3	26.00	25.00	38.00	420	F or W *	SCD 6
75	MVF075REC	NH3	26.00	25.00	38.00	550	F	SCD 6
100	MVF100REC	NH4	32.00	29.50	41.00	700	F	SCD 6
150	MVF150REC	NJ4	32.00	32.50	50.00	950	F	SCD 6
167	MVF167REC	NJ4	32.00	32.50	50.00	1150	F	SCD 6
250	MVF250REC	NJ4	32.00	32.50	50.00	1400	F	SCD 6
333	MVF333REC	NJ2	48.50	38.40	59.00	1800	F	SCD 6

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

4160 Delta Primary Volts

120/240 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVF015SECN	NH6	23.90	25.00	28.75	220	F or W *	SCD 6
25	MVF025SECN	NH6	23.90	25.00	28.75	300	F or W *	SCD 6
37.5	MVF037SECN	NH6	23.90	25.00	28.75	330	F or W *	SCD 6
50	MVF050SECN	NH3	26.00	25.00	38.00	420	F or W *	SCD 6
75	MVF075SECN	NH3	26.00	25.00	38.00	550	F	SCD 6
100	MVF100SEC	NH4	32.00	29.50	41.00	700	F	SCD 6
150	MVF150SEC	NJ4	32.00	32.50	50.00	950	F	SCD 6
167	MVF167SEC	NJ4	32.00	32.50	50.00	1150	F	SCD 6
250	MVF250SEC	NJ4	32.00	32.50	50.00	1400	F	SCD 6
333	MVF333SEC	NJ2	48.50	38.40	59.00	1800	F	SCD 6

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

ALUMINUM WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE

2400 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015RB	NH6	23.90	25.00	28.75	240	F or W *	SCD 8
30	MVK030RB	NH6	23.90	25.00	28.75	380	F or W *	SCD 10
45	MVK045RB	NH3	26.00	25.00	38.00	460	F or W *	SCD 10
75	MVK075RB	NH3	26.00	25.00	38.00	620	F	SCD 10
112.5	MVK112RB	NH4	32.00	29.50	41.00	800	F	SCD 10
150	MVK150RB	NH4	32.00	29.50	41.00	980	F	SCD 10
225	MVK225RB	NJ1	39.50	34.00	51.50	1450	F	SCD 10
300	MVK300RB	NJ1	39.50	34.00	51.50	1620	F	SCD 10
500	MVK500RB	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MVK750RB	NJ3	51.50	43.40	66.00	3150	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

2400 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015RK	NH6	23.90	25.00	28.75	240	F or W *	SCD 8
30	MVK030RK	NH6	23.90	25.00	28.75	380	F or W *	SCD 10
45	MVK045RK	NH3	26.00	25.00	38.00	460	F or W *	SCD 10
75	MVK075RK	NH3	26.00	25.00	38.00	620	F	SCD 10
112.5	MVK112RK	NH4	32.00	29.50	41.00	800	F	SCD 10
150	MVK150RK	NH4	32.00	29.50	41.00	980	F	SCD 10
225	MVK225RK	NJ1	39.50	34.00	51.50	1450	F	SCD 10
300	MVK300RK	NJ1	39.50	34.00	51.50	1620	F	SCD 10
500	MVK500RK	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MVK750RK	NJ3	51.50	43.40	66.00	3150	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

2400 Delta Primary Volts

600Y/347 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015RP	NH6	23.90	25.00	28.75	240	F or W *	SCD 8
30	MVK030RP	NH6	23.90	25.00	28.75	380	F or W *	SCD 10
45	MVK045RP	NH3	26.00	25.00	38.00	460	F or W *	SCD 10
75	MVK075RP	NH3	26.00	25.00	38.00	620	F	SCD 10
112.5	MVK112RP	NH4	32.00	29.50	41.00	800	F	SCD 10
150	MVK150RP	NH4	32.00	29.50	41.00	980	F	SCD 10
225	MVK225RP	NJ1	39.50	34.00	51.50	1450	F	SCD 10
300	MVK300RP	NJ1	39.50	34.00	51.50	1620	F	SCD 10
500	MVK500RP	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MVK750RP	NJ3	51.50	43.40	66.00	3150	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.



ALUMINUM WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE

4160 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015SB	NH6	23.90	25.00	28.75	240	F or W *	SCD 8
30	MVK030SB	NH6	23.90	25.00	28.75	380	F or W *	SCD 10
45	MVK045SB	NH3	26.00	25.00	38.00	460	F or W *	SCD 10
75	MVK075SB	NH3	26.00	25.00	38.00	620	F	SCD 10
112.5	MVK112SB	NH4	32.00	29.50	41.00	800	F	SCD 10
150	MVK150SB	NH4	32.00	29.50	41.00	980	F	SCD 10
225	MVK225SB	NJ1	39.50	34.00	51.50	1450	F	SCD 10
300	MVK300SB	NJ1	39.50	34.00	51.50	1620	F	SCD 10
500	MVK500SB	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MVK750SB	NJ3	51.50	43.40	66.00	3150	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

4160 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015SK	NH6	23.90	25.00	28.75	240	F or W *	SCD 8
30	MVK030SK	NH6	23.90	25.00	28.75	380	F or W *	SCD 10
45	MVK045SK	NH3	26.00	25.00	38.00	460	F or W *	SCD 10
75	MVK075SK	NH3	26.00	25.00	38.00	620	F	SCD 10
112.5	MVK112SK	NH4	32.00	29.50	41.00	800	F	SCD 10
150	MVK150SK	NH4	32.00	29.50	41.00	980	F	SCD 10
225	MVK225SK	NJ1	39.50	34.00	51.50	1450	F	SCD 10
300	MVK300SK	NJ1	39.50	34.00	51.50	1620	F	SCD 10
500	MVK500SK	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MVK750SK	NJ3	51.50	43.40	66.00	3150	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

4160 Delta Primary Volts

600Y/347 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015SP	NH6	23.90	25.00	28.75	240	F or W *	SCD 8
30	MVK030SP	NH6	23.90	25.00	28.75	380	F or W *	SCD 10
45	MVK045SP	NH3	26.00	25.00	38.00	460	F or W *	SCD 10
75	MVK075SP	NH3	26.00	25.00	38.00	620	F	SCD 10
112.5	MVK112SP	NH4	32.00	29.50	41.00	800	F	SCD 10
150	MVK150SP	NH4	32.00	29.50	41.00	980	F	SCD 10
225	MVK225SP	NJ1	39.50	34.00	51.50	1450	F	SCD 10
300	MVK300SP	NJ1	39.50	34.00	51.50	1620	F	SCD 10
500	MVK500SP	NJ2	48.50	38.40	59.00	2400	F	SCD 10
750	MVK750SP	NJ3	51.50	43.40	66.00	3150	F	SCD 10

For shielded units, please add the suffix "S" to the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.



COPPER WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE

2400 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015RBCN	NH6	23.90	25.00	28.75	260	F or W *	SCD 8
30	MVK030RBCN	NH6	23.90	25.00	28.75	410	F or W *	SCD 10
45	MVK045RBCN	NH3	26.00	25.00	38.00	500	F or W *	SCD 10
75	MVK075RBCN	NH3	26.00	25.00	38.00	700	F	SCD 10
112.5	MVK112RBCN	NH4	32.00	29.50	41.00	820	F	SCD 10
150	MVK150RBCN	NH4	32.00	29.50	41.00	1000	F	SCD 10
225	MVK225RBC	NJ1	39.50	34.00	51.50	1500	F	SCD 10
300	MVK300RBC	NJ1	39.50	34.00	51.50	1800	F	SCD 10
500	MVK500RBC	NJ2	48.50	38.40	59.00	2600	F	SCD 10
750	MVK750RBC	NJ3	51.50	43.40	66.00	3500	F	SCD 10

For shielded units, please replace the letter "C" with a "K" in the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

2400 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015RKC	NH6	23.90	25.00	28.75	260	F or W *	SCD 8
30	MVK030RKC	NH6	23.90	25.00	28.75	410	F or W *	SCD 10
45	MVK045RKC	NH3	26.00	25.00	38.00	500	F or W *	SCD 10
75	MVK075RKC	NH3	26.00	25.00	38.00	700	F	SCD 10
112.5	MVK112RKC	NH4	32.00	29.50	41.00	820	F	SCD 10
150	MVK150RKC	NH4	32.00	29.50	41.00	1000	F	SCD 10
225	MVK225RKC	NJ1	39.50	34.00	51.50	1500	F	SCD 10
300	MVK300RKC	NJ1	39.50	34.00	51.50	1800	F	SCD 10
500	MVK500RKC	NJ2	48.50	38.40	59.00	2600	F	SCD 10
750	MVK750RKC	NJ3	51.50	43.40	66.00	3500	F	SCD 10

For shielded units, please replace the letter "C" with a "K" in the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

2400 Delta Primary Volts

600Y/347 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015RPCN	NH6	23.90	25.00	28.75	260	F or W *	SCD 8
30	MVK030RPCN	NH6	23.90	25.00	28.75	410	F or W *	SCD 10
45	MVK045RPCN	NH3	26.00	25.00	38.00	500	F or W *	SCD 10
75	MVK075RPCN	NH3	26.00	25.00	38.00	700	F	SCD 10
112.5	MVK112RPCN	NH4	32.00	29.50	41.00	820	F	SCD 10
150	MVK150RPCN	NH4	32.00	29.50	41.00	1000	F	SCD 10
225	MVK225RPC	NJ1	39.50	34.00	51.50	1500	F	SCD 10
300	MVK300RPC	NJ1	39.50	34.00	51.50	1800	F	SCD 10
500	MVK500RPC	NJ2	48.50	38.40	59.00	2600	F	SCD 10
750	MVK750RPC	NJ3	51.50	43.40	66.00	3500	F	SCD 10

For shielded units, please replace the letter "C" with a "K" in the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.



COPPER WOUND, THREE PHASE, NEMA 3R STYLE ENCLOSURE

4160 Delta Primary Volts

208Y/120 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015SBCN	NH6	23.90	25.00	28.75	260	F or W *	SCD 8
30	MVK030SBCN	NH6	23.90	25.00	28.75	410	F or W *	SCD 10
45	MVK045SBCN	NH3	26.00	25.00	38.00	500	F or W *	SCD 10
75	MVK075SBCN	NH3	26.00	25.00	38.00	700	F	SCD 10
112.5	MVK112SBCN	NH4	32.00	29.50	41.00	820	F	SCD 10
150	MVK150SBCN	NH4	32.00	29.50	41.00	1000	F	SCD 10
225	MVK225SBCN	NJ1	39.50	34.00	51.50	1500	F	SCD 10
300	MVK300SBC	NJ1	39.50	34.00	51.50	1800	F	SCD 10
500	MVK500SBC	NJ2	48.50	38.40	59.00	2600	F	SCD 10
750	MVK750SBC	NJ3	51.50	43.40	66.00	3500	F	SCD 10

For shielded units, please replace the letter "C" with a "K" in the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

4160 Delta Primary Volts

480Y/277 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015SKCN	NH6	23.90	25.00	28.75	260	F or W *	SCD 8
30	MVK030SKCN	NH6	23.90	25.00	28.75	410	F or W *	SCD 10
45	MVK045SKCN	NH3	26.00	25.00	38.00	500	F or W *	SCD 10
75	MVK075SKCN	NH3	26.00	25.00	38.00	700	F	SCD 10
112.5	MVK112SKCN	NH4	32.00	29.50	41.00	820	F	SCD 10
150	MVK150SKCN	NH4	32.00	29.50	41.00	1000	F	SCD 10
225	MVK225SKCN	NJ1	39.50	34.00	51.50	1500	F	SCD 10
300	MVK300SKC	NJ1	39.50	34.00	51.50	1800	F	SCD 10
500	MVK500SKC	NJ2	48.50	38.40	59.00	2600	F	SCD 10
750	MVK750SKC	NJ3	51.50	43.40	66.00	3500	F	SCD 10

For shielded units, please replace the letter "C" with a "K" in the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

4160 Delta Primary Volts

600Y/347 Secondary Volts

60 Hz

kVA	Catalog Number	Case Style (Pages 260-267)	Approx. Dimensions (Inches)			Approx. Weight (Lbs.)	Mtg Type W - Wall F - Floor	Wiring Diagram (Pages 272-281)
			Width	Depth	Height			
15	MVK015SPCN	NH6	23.90	25.00	28.75	260	F or W *	SCD 8
30	MVK030SPCN	NH6	23.90	25.00	28.75	410	F or W *	SCD 10
45	MVK045SPCN	NH3	26.00	25.00	38.00	500	F or W *	SCD 10
75	MVK075SPCN	NH3	26.00	25.00	38.00	700	F	SCD 10
112.5	MVK112SPCN	NH4	32.00	29.50	41.00	820	F	SCD 10
150	MVK150SPCN	NH4	32.00	29.50	41.00	1000	F	SCD 10
225	MVK225SPCN	NJ1	39.50	34.00	51.50	1500	F	SCD 10
300	MVK300SPC	NJ1	39.50	34.00	51.50	1800	F	SCD 10
500	MVK500SPC	NJ2	48.50	38.40	59.00	2600	F	SCD 10
750	MVK750SPC	NJ3	51.50	43.40	66.00	3500	F	SCD 10

For shielded units, please replace the letter "C" with a "K" in the above part numbers.

* OPTIONAL DRIP PLATE KIT REQUIRED. SEE PAGE 270 FOR DETAILS.

SECTION 12

