



# S.S. WET-LINC™ TOTALLY ENCLOSED WASHDOWN • STAINLESS STEEL MOTORS

208-230/460 VOLTS • 3-PHASE

### Features:

- Rust-free, corrosion resistant
- Totally enclosed, paint-free exterior reduces contamination
- Long lasting components made from 300 series stainless steel (frame, base, end brackets, terminal box, shaft extension, fan cover and hardware)
- Clean design with nameplate etched on the frame
- Leak resistant double sealed bearings and shaft seals
- Multiple, repositional drains provide moisture outlet regardless of motor mounting angle
- Inverter-rated, quality UL recognized components listing and CSA
- Warranty: 18 months from manufacture date 12 months from installation, whichever comes first



### Applications:

- Food Processing
- Pharmaceutical
- Packaging
- High Humidity Environments
- Chemical

### C-FACE WITH FEET

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
1/3	1800	56C	78.5	1.15	208-230/460	SRNWA4SO.33TC6-26AP21	<b>LM29189</b>	D-191201	27	\$644	LT-1A
1/2	1800	56C	81.5	1.15	208-230/460	SRNWA4SO.5TC6-26AP21	<b>LM29191</b>	D-191204	30	664	LT-1A
3/4	1800	56C	82.5	1.15	208-230/460	SRNWA4SO.75TC6-26AP21	<b>LM29193</b>	D-191207	35	767	LT-1A
1	1800	56HC	82.5	1.15	208-230/460	SRFWA4S1TC6026AP21	<b>LM29213</b>	D-191291	44	800	LT1-A
	1800	140TC	82.5	1.15	208-230/460	SSFWA4S1TC6026AP21	<b>LM29214</b>	D-191211	39	861	LT1-B
	1800	56C	81.5	1.15	208-230/460	SRNWA4S1TC6026AP21	<b>LM29601</b>	D-G191212	45	797	LT1-A
1 1/2	1800	56HC	84.0	1.15	208-230/460	SRFWA4S1.5TC6026AP21	<b>LM29217</b>	D-191217	45	834	LT1-A
	1800	140TC	84.0	1.15	208-230/460	SSFWA4S1.5TC6026AP21	<b>LM29218</b>	D-G191218	46	896	LT1-B
2	1800	56HC	84.0	1.15	208-230/460	SRFWA4S2TC6026AP21	<b>LM29221</b>	D-191223	49	951	LT1-A
	1800	140TC	84.0	1.15	208-230/460	SSFWA4S2TC6026AP21	<b>LM29222</b>	D-G191224	53	1064	LT1-B

### C-FACE FOOTLESS

HP	SYN RPM	Frame	FL Nom Eff (%)	SF	Volts	Model Number	Product Number	Notes (see page 306)	Approx Shpg Wght (lbs)	List Price	Mult Sym
1/3	1800	56C	78.5	1.15	208-230/460	SRNWA4S0.33TCN6026AP21	<b>LM29190</b>	D-191202	22	\$639	LT1-A
1/2	1800	56C	81.5	1.15	208-230/460	SRNWA4S0.5TCN6026AP21	<b>LM29192</b>	D-191205	23	657	LT1-A
3/4	1800	56C	82.5	1.15	208-230/460	SRNWA4S0.75TCN6026AP21	<b>LM29194</b>	D-191208	31	765	LT1-A
1	1800	56C	82.5	1.15	208-230/460	SRFWA4S1TCN6026AP21	<b>LM29215</b>	D-191290	37	797	LT1-A
	1800	56C	81.5	1.15	208-230/460	SRNWA4S1TCN6026AP21	<b>LM29600</b>	D-191213	37	800	LT1-A
	1800	140TC	82.5	1.15	208-230/460	SSFWA4S1TCN6026AP21	<b>LM29216</b>	D-191214	38	821	LT1-B
1 1/2	1800	56C	84	1.15	208-230/460	SRFWA4S1.5TCN6026AP21	<b>LM29219</b>	D-191219	44	831	LT1-A
	1800	140TC	84	1.15	208-230/460	SSFWA4S1.5TCN6026AP21	<b>LM29220</b>	D-191220	45	854	LT1-B
2	1800	56C	84	1.15	208-230/460	SRFWA4S2TCN6026AP21	<b>LM29223</b>	D-191225	51	948	LT1-A
	1800	140TC	84	1.15	208-230/460	SSFWA4S2TCN6026AP21	<b>LM29224</b>	D-191226	52	977	LT1-B

Prices and data subject to change without notice.

D – items to be deleted once inventory is depleted. Replaced with the listed LEESON catalog number .

Product numbers in red are STOCK items.