


AS-interface®, *minifast*® Conduit Adapters

- Gasket and Mounting Screws Provided
- Same Housing Style for Single or Double Port




Housing	Part Number	Specs	Application	Pinout
	BCA 25-M123	Nylon Housing 300 V, 9 A -40° to +75°C	Attaches to standard conduit body* for transition to 4-wire (7/8-16UN) <i>minifast</i> connector *Crouse Hinds 3/4" Form 8, Mark 9 or equivalent	<p>Female</p>
	BCA 25-M223	Nylon Housing 300 V, 9 A -40° to +75°C		

1-port Wiring Diagram



2-port Wiring Diagram




AS-interface®, eurofast® Conduit Adapters

- Gasket and Mounting Screws Provided
- Same Housing Style for Single or Double Port



Housing	Part Number	Specs	Application	Pinout
	BCA 25-E123	Nylon Housing 250 V, 4 A -40° to +75°C	Attaches to standard conduit body* for transition to 4-wire (M12x1) eurofast connector	<p>Female</p>
	BCA 25SC-E123	<p>Electrical</p> <ul style="list-style-type: none"> • Short-circuit protection: 280 mA • Open circuit voltage: 33 VDC • Current consumption: 11 mA <p>Diagnostics</p> <ul style="list-style-type: none"> • LED indicators Power: Green = On Short-circuit: Red = Shorted 		
	BCA 25-E223	Nylon Housing 250 V, 4 A -40°C to +75°C	*Crouse Hinds 3/4" Form 8, Mark 9 or equivalent	
	BCA 25SC-E223	<p>Electrical</p> <ul style="list-style-type: none"> • Short-circuit protection: 280 mA • Open circuit voltage: 33 VDC • Current consumption: 11 mA <p>Diagnostics</p> <ul style="list-style-type: none"> • LED indicators Power: Green = On Short-circuit: Red = Shorted 		

1-port Wiring Diagram



2-port Wiring Diagram

