

euromast<sup>®</sup> Conduit Adapters

euromast

- Attaches to Standard Conduit Bodies for Transition to 5-wire *minifast*<sup>®</sup> Connectors
- Gasket and 8-32 x 1/2 Mounting Screws Included
- IP 67 Protection (only when all receptacles are mated or covered with plugs)



Drawing	Part Number	Specifications	Application	Pinout	Wiring Diagram
	CA-1/FK 4.5		Attaches to standard conduit body for transition to 5-wire euromast connector		
	CA-2/FK 4.5	Nylon housing 80°C 250 V, 4 A	Attaches to standard conduit body for transition to 5-wire euromast connector		

Standard receptacle housing material is nickel plated brass "CA-1(2)/FK 4.5"; "CA-1(2)/FKV 4.5" indicates stainless steel.

**eurofast® Adapters**

- Converts *eurofast* to *minifast*®
- Rugged Metal Connector
- NEMA 1, 3, 4



Drawing	Part Number	Cable	Features	Pinout
	RSM 40-FK 4.4	80°C 250 V 4 A	Female <i>eurofast</i> to male <i>minifast</i> ® adapter, 4-pin	
	RSM 50-FK 4.5	80°C 250 V 4 A	Female <i>eurofast</i> to male <i>minifast</i> adapter, 5-pin	