


microfast® Adapters

Housing Style	Part Number	Cable	Features	Pinout
	B3131-*	Nickel plated brass 3x26 AWG leads 80°C 250 V, 4.0 A	Mates with 3-pin cordsets, 1/2 - 14NPSM thread	<ol style="list-style-type: none"> GN BN BU
	B3141-*	Nickel plated brass 4x22 AWG leads 80°C 250 V, 4.0 A	Mates with 4-pin cordsets, 1/2 - 14NPSM thread	<ol style="list-style-type: none"> RD/BK RD/WH RD GN
	B3151-*	Nickel plated brass 5x26 AWG leads 80°C 250 V, 4.0 A	Mates with 5-pin cordsets, 1/2 - 14NPSM thread	<ol style="list-style-type: none"> RD/WH RD GN RD/YE RD/BK
	B3131-PG9-*	Nickel plated brass 3x26 AWG leads 80°C 250 V, 4.0 A	Mates with 3-pin cordsets, PG 9 thread	<ol style="list-style-type: none"> GN BN BU
	B3141-PG9-*	Nickel plated brass 4x22 AWG leads 80°C 250 V, 4.0 A	Mates with 4-pin cordsets, PG 9 thread	<ol style="list-style-type: none"> RD/BK RD/WH RD GN
	B3151-PG9-*	Nickel plated brass 5x26 AWG leads 80°C 250 V, 4.0 A	Mates with 5-pin cordsets, PG 9 thread	<ol style="list-style-type: none"> RD/WH RD GN RD/YE RD/BK
	RKM 30/SB3	Nickel plated brass 80°C 250 V, 4.0 A	Female minifast® to male microfast adapter, 3-pin	

RKM 30/SB3 - Wiring Diagram



- For Use in Sensors and Custom Receptacles
- Compatible with Standard *microfast* Cordsets



Housing Style	Part Number	Cable	Features	Pinout
	ESBW 3 (10/BAG)	Nylon Solder Cup, accepts up to 22 AWG 80°C 250 V, 4.0 A	Up to 3 conductors	
	ESBW 4 (10/BAG)	Nylon Solder Cup, accepts up to 22 AWG 80°C 250 V, 4.0 A	Up to 4 conductors	
	ESBW 5 (10/BAG)	Nylon Solder Cup, accepts up to 22 AWG 80°C 250 V, 4.0 A	Up to 5 conductors	
	SB-CC (10/BAG)	Polypropylene	Mates to female cordsets, receptacles and junction boxes	