









2-6 Wire *microfast*® Receptacles, Front Mount, 1/2-14 NPSM Threads

- Male Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
 <b>FSB .. 14.5</b>	FSB 2-*/14.5	UL, CSA 2x22 AWG 105°C	1/2 - 14 NPSM Threads	1. BN 2. BU 
	FSB 3-*/14.5	UL, CSA 3x22 AWG 105°C		1. GN 2. RD/BK 3. RD/WH 
	FSB 3-*/14.5/S690	UL, CSA 3x18 AWG 105°C		
	FSB 4-*/14.5	UL, CSA 4x22 AWG 105°C		1. RD/BK 2. RD/WH 3. RD 4. GN 
	FSB 5-*/14.5	UL, CSA 5x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 
	FSB 5-*/14.5/S690	UL, CSA 5x18 AWG 105°C		
	FSB 6-*/14.5	UL, CSA 6x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 6. RD/BU 

See page F23 for dimensional drawings.









\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass."FSB ..".

To specify PVC jacketed cable, add "/S717" to the end of the part number.

2-6 Wire *microfast*® Receptacles, Front Mount, 1/2-14 NPSM Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
 <p>FKB .. 14.5</p>	FKB 2-*/14.5	UL, CSA 2x22 AWG 105°C	1/2 - 14 NPSM Threads	1. BN 2. BU 
	FKB 3-*/14.5	UL, CSA 3x22 AWG 105°C		1. GN 2. RD/BK 3. RD/WH 
	FKB 3-*/14.5/S690	UL, CSA 3x18 AWG 105°C		
	FKB 4-*/14.5	UL, CSA 4x22 AWG 105°C		1. RD/BK 2. RD/WH 3. RD 4. GN 
	FKB 5-*/14.5	UL, CSA 5x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 
	FKB 5-*/14.5/S690	UL, CSA 5x18 AWG 105°C		
	FKB 6-*/14.5	UL, CSA 6x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 6. RD/BU 

Receptacles

See page F23 for dimensional drawings.

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.








Standard housing material is nickel plated brass."FKB ..".

To specify PVC jacketed cable, add "/S717" to the end of the part number.

2-6 Wire *microfast*® Receptacles, Front Mount, 1/2-14 NPT Threads

- Male Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
 <b>FSB ..14.5/NPT</b>	FSB 2-*/14.5/NPT	UL, CSA 2x22 AWG 105°C	1/2 - 14 NPT Threads	1. BN 2. BU 
	FSB 3-*/14.5/NPT	UL, CSA 3x22 AWG 105°C		1. GN 2. RD/BK 3. RD/WH 
	FSB 4-*/14.5/NPT	UL, CSA 4x22 AWG 105°C		1. RD/BK 2. RD/WH 3. RD 4. GN 
	FSB 5-*/14.5/NPT	UL, CSA 5x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 
	FSB 5-*/14.5/NPT/S690	UL, CSA 5x18 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 6. RD/BU 
	FSB 6-*/14.5/NPT	UL, CSA 6x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 6. RD/BU 

See page F23 for dimensional drawings.

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.







Standard housing material is nickel plated brass."FSB..".

To specify PVC jacketed cable, add "/S717" to the end of the part number.

**2-6 Wire *microfast*® Receptacles, Front Mount, 1/2-14 NPT Threads**

- Female Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
 <p>FKB .. 14.5/NPT</p>	FKB 2-*/14.5/NPT	UL, CSA 2x22 AWG 105°C	1/2 - 14 NPT Threads	1. BN 2. BU 
	FKB 3-*/14.5/NPT	UL, CSA 3x22 AWG 105°C		1. GN 2. RD/BK 3. RD/WH 
	FKB 4-*/14.5/NPT	UL, CSA 4x22 AWG 105°C		1. RD/BK 2. RD/WH 3. RD 4. GN 
	FKB 5-*/14.5/NPT	UL, CSA 5x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 
	FKB 6-*/14.5/NPT	UL, CSA 6x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 6. RD/BU 

Receptacles

See page F24 for dimensional drawings.

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.

Standard housing material is nickel plated brass..FKB ..".

To specify PVC jacketed cable, add "/S717" to the end of the part number.

2-3 Wire *microfast*® Receptacles, Front Mount, 1/4-18 NPT Threads

- Male Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Housing Style	Part Number	Lead Specs.	Features	Pinout
	FSB 2-*/18.25	UL, CSA 2x22 AWG 105°C	1/4 - 18 NPT Threads	1. BN 2. BU 
	FSB 3-*/18.25/S649	UL, CSA 3x22 AWG 105°C		1. GN 2. BK 3. WH
	FSB 3-*/18.25/S662	UL, CSA 3x18 AWG 105°C		
	FSB 3-*/18.25	UL, CSA 3x22 AWG 105°C		
	FSB 3-*/18.25/S690	UL, CSA 3x18 AWG 105°C		1. YE 2. GN 3. BN
	FSB 3-*/18.25/S881	UL, CSA 3x22 AWG 105°C		






See page F23 for dimensional drawings.

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.  
Standard housing material is nickel plated brass. "FSB ..". "FSBV.." indicates 316 stainless steel housing.  
To specify PVC jacketed cable, add "/S717" to the end of the part number.

## 4-6 Wire *microfast*® Receptacles, Front Mount, 1/4-18 NPT Threads

- Male Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Housing Style	Part Number	Lead Specs.	Features	Pinout	
 <p>FSB ..18.25</p>	FSB 4-*/18.25/S621	UL, CSA 4x18 AWG 105°C	1/4-18 NPT threads	<ol style="list-style-type: none"> <li>GY1</li> <li>GY2</li> <li>GY3</li> <li>GY4</li> </ol>	
	FSB 4-*/18.25	UL, CSA 4x22 AWG 105°C		<ol style="list-style-type: none"> <li>RD/BK</li> <li>RD/WH</li> <li>RD</li> <li>GN</li> </ol>	
	FSB 4-*/18.25/S727	UL, CSA 4x22 AWG 105°C		<ol style="list-style-type: none"> <li>BN</li> <li>BU</li> <li>BK</li> <li>WH</li> </ol>	
	FSB 5-*/18.25	UL, CSA 5x22 AWG 105°C		<ol style="list-style-type: none"> <li>RD/WH</li> <li>RD</li> <li>GN</li> <li>RD/YE</li> <li>RD/BK</li> </ol>	
	FSB 5-*/18.25/S690	UL, CSA 5x18 AWG 105°C		<ol style="list-style-type: none"> <li>RD/WH</li> <li>RD</li> <li>GN</li> <li>RD/YE</li> <li>RD/BK</li> <li>RD/BU</li> </ol>	
	FSB 6-*/18.25	UL, CSA 6x22 AWG 105°C		<ol style="list-style-type: none"> <li>RD/WH</li> <li>RD</li> <li>GN</li> <li>RD/YE</li> <li>RD/BK</li> <li>RD/BU</li> </ol>	

Receptacles







See page F23 for dimensional drawings.

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.  
 Standard housing material is nickel plated brass. "FSB ..". "FSBV.." indicates 316 stainless steel housing.  
 To specify PVC jacketed cable, add "/S717" to the end of the part number.

2-6 Wire *microfast*® Receptacles, Front Mount, 1/4-18 NPT Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Housing Style	Part Number	Lead Specs.	Features	Pinout
 <b>FKB ..18.25</b>	FKB 2-*/18.25	UL, CSA 2x22 AWG 105°C	<i>1/4 - 18 NPT Threads</i>	1. BN 2. BU 
	FKB 3-*/18.25	UL, CSA 3x22 AWG 105°C		1. GN 2. RD/BK 3. RD/WH 
	FKB 3-*/18.25/S690	UL, CSA 3x18 AWG 105°C		
	FKB 3-*/18.25/S662	UL, CSA 3x18 AWG 105°C		1. GN 2. BK 3. WH 
	FKB 4-*/18.25	UL, CSA 4x22 AWG 105°C		1. RD/BK 2. RD/WH 3. RD 4. GN 
	FKB 5-*/18.25	UL, CSA 5x22 AWG 105°C		1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK 
	FKB 5-*/18.25/S690	UL, CSA 5x18 AWG 105°C		
	FKB 6-*/18.25	UL, CSA 6x22 AWG 105°C		

See page F24 for dimensional drawings.




\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths.

Standard housing material is nickel plated brass. "FKB ..". "FKBV .." indicates 316 stainless steel housing.

## 3 and 5-Wire *microfast*® Receptacles, Back Panel Mount, 11/16-24 Threads

- Female Receptacles
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Drawing Number	Part Number	Lead Specs.	Features	Pinout
 <p>7</p> <p>FKBP ..</p>	FKBP 3-*	UL, CSA 3x18 AWG 80°C	11/16-24 Threads	 <p>1. GN 2. RD/BK 3. RD/WH</p>
	FKBP 5-*	UL, CSA 5x18 AWG 80°C		 <p>1. RD/WH 2. RD 3. GN 4. RD/YE 5. RD/BK</p>

Receptacles

See page F24 for dimensional drawings.

\* Length in meters. Standard lead length is 0.5 Meters. Consult factory for other lengths. Standard housing material is nickel plated brass.

3, 4 and 5-Wire *microfast*® Bulkhead Feed-Thru Receptacles

- Shielded
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection
- 250 V, 4 A



Drawing Number	Part Number	Connector Specs.	Features	Pinout
	FKB FSB 3	Nickel Plated Brass 3-pin 105°C	1/2 - 20UNF Threads	
	FKB FSB 4	Nickel Plated Brass 4-pin 105°C		
	FKB FSB 5	Nickel Plated Brass 5-pin 105°C		

See page F24 for dimensional drawings.

Standard housing material is nickel plated brass. "FKB FSB ..". "FKBV FSBV.." indicates 316 stainless steel housing.