

minifast® Conduit Adapters, 1 Port

- Attaches to Standard Conduit Bodies for Transition to 3-5 Wire minifast Connectors
- Gasket and 8-32 x 1/2 Mounting Screws
- IP 67 Protection (only when all receptacles are mated or covered with plugs)



| Drawing Number | Part Number | Cable | Application | Wiring Diagram |
|----------------|-------------|------------------------------------|---|----------------|
| | CA-1/RKF 30 | Nylon Housing 80°C 250 V, 9A | Attaches to standard conduit body for transition to 3-wire minifast connector | |
| | CA-1/RKF 40 | | Attaches to standard conduit body for transition to 4-wire minifast connector | |
| | CA-1/RKF 50 | | Attaches to standard conduit body for transition to 5-wire minifast connector | |


Standard receptacle housing material is nickel plated brass. "RKF"; "RKfV" indicates 316 stainless steel.
Example: CA-2/RKfV 50.








Pinouts

| Female | | | Male | | |
|--------|-------|-------|-------|-------|-------|
| | | | | | |
| 3-Pin | 4-Pin | 5-Pin | 3-Pin | 4-Pin | 5-Pin |

minifast® Conduit Adapters, 2 Port

- Attaches to Standard Conduit Bodies for Transition to 3-5 Wire minifast Connectors
- Gasket and 8-32 x 1/2 Mounting Screws
- IP 67 Protection (only when all receptacles are mated or covered with plugs)



| Drawing Number | Part Number | Cable | Application | Wiring Diagram |
|--|------------------|------------------------------------|---|---|
|  | CA-2/RKF 30 | Nylon Housing 80°C 250 V, 9A | Attaches to standard conduit body for transition to 3-wire minifast connector |  |
| | CA-2/RKF 30/S651 | | Attaches to standard conduit body for transition to 3-wire minifast connector, parallel wired |  |
| | CA-2/RKF 40 | | Attaches to standard conduit body for transition to 4-wire minifast connector |  |
| | CA-2/RKF 40/S651 | | Attaches to standard conduit body for transition to 4-wire minifast connector, parallel wired |  |
| | CA-2/RKF 50 | | Attaches to standard conduit body for transition to 5-wire minifast connector |  |
| | CA-2/RKF 50/S651 | | Attaches to standard conduit body for transition to 5-wire minifast connector, parallel wired |  |

Field Wireables

Standard receptacle housing material is nickel plated brass. "RKF"; "RKFV" indicates 316 stainless steel.
 Example: CA-2/RKFV 50.
 For pinouts see bottom of page E87.