

minifast® Quick Disconnect Adapters

- Adapt to Standard minifast Cordsets
- Available w/NPSM or PG 9 Threads



	B2131-*M	Nylon 300 V/ 4.0 A 3x22 AWG 70°C	Mates with 3-pin cordsets, 1/2 - 14NPSM Threads	1. Gn 2. Bn 3. Bu	
	B1131-*M	Nickel plated brass 300 V/ 4.0 A 3x22 AWG 70°C	Mates with 3-pin cordsets, 1/2 - 14NPSM Threads		
	B2131-*M/S523	Nylon 300 V/ 4.0 A A3x22 AWG 70° C	Mates with 3-pin cordsets, 1/2 - 14NPSM Threads	1. Bk 2. Bn 3. Bu	
	B2141-*M	Nylon 300 V/ 4.0 A 4x22 AWG 70°C	Mates with 4-pin cordsets, 1/2 - 14NPSM Threads	1. Bn 2. Wh 3. Bu 4. Bk	
	B1141-*M	Nickel plated brass 300 V/ 4.0 A 4x22 AWG 70°C	Mates with 4-pin cordsets, 1/2 - 14NPSM Threads		
	B1131-PG9-*M	Nickel plated brass 300 V/ 4.0 A 3x22 AWG 70°C	Mates with 3-pin cordsets, PG 9 Threads	1. Gn 2. Bn 3. Bu	
	B1141-PG9-*M	Nickel plated brass 300 V/ 4.0 A 4x22 AWG 70°C	Mates with 4-pin cordsets, PG 9 Threads	1. Bn 2. Wh 3. Bu 4. Bk	
	B1151-PG9-*M	Nickel plated brass 300 V/ 4.0 A 5x22 AWG 70°C	Mates with 5-pin cordsets, PG 9 Threads	1. Bn 2. Wh 3. Bu 4. Bk 5. Gn	

minifast® Quick Disconnect Adapters

- Convert *minifast* to *eurofast*® or *microfast*®
- Rugged Metal Connector



Housing Style	Part Number	Specs	Features	Wiring Diagram
	RSM 40-FK 4.4	Nickel plated brass 250 V, 4 A 80°C	Female <i>eurofast</i> ®, male <i>minifast</i> ®, 4-pin	
	RSM 50-FK 4.5	Nickel plated brass 250 V, 4 A 80°C	Female <i>eurofast</i> , male <i>minifast</i> , 5-pin	
	RKM 30/SB3	Nickel plated brass 250 V, 4 A 80°C	Female <i>minifast</i> , male <i>microfast</i> ®, 3-pin	

Accessories

Pinouts

Female			Male		
3-Pin <i>minifast</i>	4-Pin <i>eurofast</i>	5-Pin <i>eurofast</i>	3-Pin <i>microfast</i>	4-Pin <i>minifast</i>	5-Pin <i>minifast</i>