

3 and 4-Wire M8 *pico fast*® Cordsets, Threaded Coupling Nut, Shielded

- Straight Female Connectors
- Shield to Coupling Nut
- IEC IP 67 Protection
- 125 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
<p>PKGS ..M** 1.319 [33.5] 0.378 [9.6] M8x1</p>	PKGS 3M-*	AWM PVC Yellow 3x24 AWG 105°C Cable #RF51422-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 3. BU 4. BK
	PKGS 3M-*/S90	AWM PUR Black 3x24 AWG 90°C Cable #RF51423-*M [†]		
	PKGS 4M-*	AWM PVC Yellow 4x26 AWG 105°C Cable #RF51424-*M [†]		1. BN 2. WH 3. BU 4. BK
	PKGS 4M-*/S90	AWM PUR Black 4x26 AWG 90°C Cable #RF51425-*M [†]		

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling material is nickel plated brass.

† See Section N for *reelfast*® cable information.

3 and 4-Wire M8 picofast® Cordsets, Threaded Coupling Nut, Shielded

- Right Angle Male Connectors
- Shield to Coupling Nut
- IEC IP 67 Protection
- 125 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout	
	PSWS 3M-*	AWM PVC Yellow 3x24 AWG 105°C Cable #RF51422-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	1. BN 3. BU 4. BK	
	PSWS 3M-*/S90	AWM PUR Black 3x24 AWG 90°C Cable #RF51423-*M [†]			
	PSWS 4M-*	AWM PVC Yellow 4x26 AWG 105°C Cable #RF51424-*M [†]		1. BN 2. WH 3. BU 4. BK	
	PSWS 4M-*/S90	AWM PUR Black 4x26 AWG 90°C Cable #RF51425-*M [†]			

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling material is nickel plated brass.

† See Section N for **reelfast**® cable information.

3 and 4-Wire M8 picofast® Cordsets, Threaded Coupling Nut, Shielded

- Right Angle Female Connectors
- Shield to Coupling Nut
- IEC IP 67 Protection
- 125 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout	
<p>PKWS ..M**</p> <p>1.154 [29.3]</p> <p>0.378 [9.6]</p> <p>M8x1</p> <p>0.807 [20.5]</p>	PKWS 3M-*	AWM PVC Yellow 3x24 AWG 105°C Cable #RF51422-*M†	RFI/EMI Shielding Tied to Coupling Nut	1. BN 3. BU 4. BK	
	PKWS 3M-*/S90	AWM PUR Black 3x24 AWG 90°C Cable #RF51423-*M†			
	PKWS 4M-*	AWM PVC Yellow 4x26 AWG 105°C Cable #RF51424-*M†		1. BN 2. WH 3. BU 4. BK	
	PKWS 4M-*/S90	AWM PUR Black 4x26 AWG 90°C Cable #RF51425-*M†			

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling material is nickel plated brass.

† See Section N for **reelfast**® cable information.

3 and 4-Wire M8 *pico fast*® Cordsets, Threaded Coupling Nut, Shielded

- Straight Male Connectors
- Shield to Coupling Nut
- IEC IP 67 Protection
- 125 V, 4 A



Housing Style	Part Number	Cable	Features	Pinout
<p>PSGS ..M**</p> <p>1.579 [40.1]</p> <p>0.378 [9.6]</p> <p>M8x1</p>	PSGS 3M-*	AWM PVC Yellow 3x24 AWG 105°C Cable #RF51422-*M [†]	RFI/EMI Shielding Tied to Coupling Nut	<p>1. BN 3. BU 4. BK</p>
	PSGS 3M-*/S90	AWM PUR Black 3x24 AWG 90°C Cable #RF51423-*M [†]		
	PSGS 4M-*	AWM PVC Yellow 4x26 AWG 105°C Cable #RF51424-*M [†]		<p>1. BN 2. WH 3. BU 4. BK</p>
	PSGS 4M-*/S90	AWM PUR Black 4x26 AWG 90°C Cable #RF51425-*M [†]		

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling material is nickel plated brass.

† See Section N for *reelfast*® cable information.