

**14 and 19-Pin M16 versafast® Field Wireable, In-line Connectors**

- Male Connectors
- For use with Custom Wiring or Junction Boxes
- IEC IP 67 Protection



Housing Style	Part Number	Specs	Features	Pinout
<p><b>RBS ..</b></p>	BS 14-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder cup, accepts up to 14x24 AWG conductors 85°C 60 VAC/DC, 3.0 A	Mates with picofast junction boxes, unshielded	
	BS 19-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder cup, accepts up to 19x24 AWG conductors 85°C 60 VAC/DC, 3.0 A	Mates with picofast junction boxes, unshielded	
<p><b>WBS ..</b></p>	WBS 14-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder cup, accepts up to 14x24 AWG conductors 85°C 60 VAC/DC, 3.0 A	Mates with picofast junction boxes, unshielded	
	WBS 19-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder cup, accepts up to 19x24 AWG conductors 85°C 60 VAC/DC, 3.0 A	Mates with picofast junction boxes, unshielded	

14 and 19-Pin M16 versafast® Field Wireable, In-line Connectors

- Female Connectors
- For use with Custom Wiring or Junction Boxes
- IEC IP 67 Protection



Housing Style	Part Number	Specs	Features	Pinout
<p><b>RBK ..</b></p>	BK 14-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder cup, accepts up to 14x24 AWG conductors 85° C 60 VAC/DC, 3.0 A	Mates with picofast junction boxes, unshielded	
	BK 19-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder cup, accepts up to 19x24 AWG conductors 85° C 60 VAC/DC, 3.0 A	Mates with picofast junction boxes, unshielded	
<p><b>WBKS ..</b></p>	WBKS 14-0	Nickel Plated Cast Zinc PG 9 cable gland, accepts 6-8 mm cable diameter Solder cup, accepts up to 14x24 AWG conductors 85° C 60 VAC/DC, 3.0 A	Mates with picofast junction boxes, shielded	

Field Wireables

**12-pin M16 *versa*fast® Field Wireable, In-line Connectors**

- Male and Female Connectors
- Standard Nylon and Shielded
- IEC IP 67 Protection



Housing Style	Part Number	Cable	Features	Pinout
<p><b>BS ..</b></p>	BS 12-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder Cup, accepts up to 12x24 AWG conductors 85°C 60 VDC/VAC, 3 A	Mates with 12-pin cordsets and receptacles	
<p><b>BSS ..</b></p>	BSS 12-0	Stainless steel PG 9 cable gland, accepts 6-8 mm cable diameter Solder Cup, accepts up to 12x24 AWG conductors 85°C 60 VDC/VAC, 3 A	Mates with 12-pin cordsets and receptacles, <i>Shielded</i>	
<p><b>BK ..</b></p>	BK 12-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter Solder Cup, accepts up to 12x24 AWG conductors 85°C 60 VAC/VDC, 3 A	Mates with 12-pin cordsets and receptacles	
<p><b>BKS ..</b></p>	BKS 12-0	Stainless steel PG 9 cable gland, accepts 6-8 mm cable diameter Solder Cup, accepts up to 12x24 AWG conductors 85°C 60 VDC/VAC, 3 A	Mates with 12-pin cordsets and receptacles, <i>Shielded</i>	