

# Inductive Cylinder Position Sensors



Housing Style	Part Number	ID Number	Linear Operating Distance (mm)	Response Freq. (Hz)	Output
<b>23 mm - Embeddable, T Groove Pneumatic Cylinders <i>picofast</i>® Quick Disconnect</b> 	WIM45-UNTL-LIU5X2-0.3M-PSG 4M	M1536620	45	N/A	4-Wire DC Current and Voltage
<b>23 mm - Embeddable, T Groove Pneumatic Cylinders <i>euofast</i>® Quick Disconnect</b> 	WIM45-UNTL-0.3-BIM-UNT-LUAP6X4-H1141	M1536623	45	N/A	4-Wire DC Current and Voltage
<b>23 mm - Embeddable, T Groove Pneumatic Cylinders <i>euofast</i>® Quick Disconnect</b> 	WIM45-UNTL-LIU5X2-0.3M-RS 4	M1536621	45	N/A	4-Wire DC Current and Voltage

Inches (mm)

For detailed sensor specifications see Section M.  
Normally Closed versions available upon request, consult factory.



Voltage	Output Voltage/Current	Operating Temp. (°C)	Protection	Slew Rate V/ms, mA/ms	Housing	Face	Mating Cord, Cable Length/Mat.	Wiring Diagram #	Wiring Diagrams
15-30 VDC	0-10 V/4-20 mA	-25 to +70	IP 67	20, 32	PA12	PA12	PKG 4M-*	1	<p><b>Diagram 1</b></p> <p><b>Diagram 2</b></p>
15-30 VDC	0-10 V/4-20 mA	-25 to +70	IP 67	20, 32	PA12	PA12	RK 4.4T-*	2	
15-30 VDC	0-10 V/4-20 mA	-25 to +70	IP 67	20, 32	PA12	PA12	RK 4.4T-*	1	

\* Length in meters.

For material descriptions see page M36.