

Multi level terminals

In hazardous area applications, the installation instructions and the rated data specifications for accessories given in the technical appendix must be followed.

Width/Length/height with TS35x7.5	mm
max. current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²


Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm ²
Rated impulse voltage / Pollution severity	kV / -
UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
solid / stranded	mm ²
flexible / Stranded wire with end ferrules	mm ²
Twin wire-end ferrule	mm ²
Stripping length / Blade size	mm ²
Note	

Ordering data

Version	
Dark beige Wemid	
Blue Wemid	
Note	

Accessories

Pluggable cross-connection	Version
	2-pole
	3-pole
	4-pole
	10-pole
	20/24-pole
End plate / Partition	Dark beige Wemid
	Blue Wemid
End bracket	Dark beige Wemid
Test adapter	Standard
	With assembly peg
Screwdriver	Standard
Reducing sleeves	For conductors < 0.5mm ² / AWG 20
	For conductors < 1mm ² / AWG 18
Identification systems	Marking tags
For detailed information on other accessories and applications, refer to the „Accessories“ section	

PMAK 4

4 mm²

Motor-supply terminal



5.1 x 103.9 x 79.1
32 / 6
0.5...6

IEC	UL	CSA
400	300	300
32	30	30
4		
	6 / 3	
	V-0	
Rated connection		
0.5...6		
0.5...4 / 0.5...4		
12 / 0.4 x 2.5		

Type	Qty.	Order No.
PMAK 4		1221340000

PMAK 4 800V

4 mm²

Motor-supply terminal



6.1 x 107.5 x 82.6
32 / 6
0.5...6

IEC	UL	CSA
800	600	600
30	30	30
4		
	8 / 3	
	V-0	
Rated connection		
0.5...6		
0.5...4 / 0.5...4		
12 / 0.4 x 2.5		

Type	Qty.	Order No.
PMAK 4 800V		1221350000

With pre-assembled end plate and a width of 6.1 mm!

Type	Qty.	Order No.
ZEW 35		9540000000
SDI 0.4x2.5x75		9008370000
DEK 5/5 / WS 10/5		