

## Double level terminals

Identical profiles from 2.5 to 10 mm<sup>2</sup> with uniform end and partition plates. An unsurpassed combination of many advantages!

Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.

In hazardous area applications, the installation instructions and the rated data specifications for accessories given in the technical appendix must be followed.

Width/Length/height with TS35x7.5	mm
max. current / max. cond. cross-section	A/mm <sup>2</sup>
Max. clamping range	mm <sup>2</sup>




### Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm <sup>2</sup>
Rated impulse voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
solid / stranded	mm <sup>2</sup>
flexible / Stranded wire with end ferrules	mm <sup>2</sup>
Tightening torque range (clamping screw)	
Stripping length / Blade size	mm/-
2 conductors with same cross-section (H05V/H07V)	
solid / stranded	mm <sup>2</sup>
flexible / Stranded wire with end ferrules	mm <sup>2</sup>
Note	

### Ordering data

Version	
	Dark beige Wemid
	Blue Wemid
Note	

### Accessories


Pluggable cross-connection	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
Screwable cross-connection	
	2-pole
	3-pole
	4-pole
	10-pole
End plate / partition	
	Dark beige Wemid
	Blue Wemid
	Dark beige Wemid
End bracket	
	Dark beige Wemid
Cover	
	With lightning flash symbol
	blank
Marking systems	
	(see assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications, refer to the „Accessories“ section	

## WDK 2.5 ZQV

2.5 mm<sup>2</sup>

### Plug-in cross-connection



5.1 x 65.4 x 63	
<b>32 / 4</b>	
<b>0.05...4</b>	

IEC 60947-7-1			
IEC	UL	CSA	
400	300	300	
24	20	25	
2.5	AWG 30...12	AWG 26...12	
6 / 3			
A3 / V-0			
KEMA 98ATEX1685 U			
Rated connection			
0.5...4 / 1.5...4			
0.5...4 / 0.5...2.5			
0.4...0.6 Nm (M 2.5)			
10 / 0.6 x 3.5 mm			
0.5...1.5			
0.5...1.5 / 0.5...1.5			
2.5 mm <sup>2</sup> conductor with wire end ferrule plus plastic collar only with collar optimised for diameter (order No. 1333100000, 500 pcs)			

Type	Qty	Order No.
WDK 2.5 ZQV	100	1041100000
WDK 2.5 ZQV BL	100	1041180000
Rated voltage 400V when using cross-connection ZQV		
See section „W-series accessories“ for colours available.		

Type	current	Qty	Order No.
ZQV 2.5N/2 GE	24 A	60	1693800000
ZQV 2.5N/3 GE	24 A	60	1693810000
ZQV 2.5N/4 GE	24 A	60	1693820000
ZQV 2.5N/10 GE	24 A	20	1693880000
ZQV 2.5N/20 GE	24 A	20	1909000000
Width			
WAP WDK2.5	1.5 mm	20	1059100000
WAP WDK2.5 BL	1.5 mm	20	1059180000
WTW EN	3 mm	20	1058800000
WEW 35/2	8 mm	100	1061200000
WAD 4 GE BED	4 mm	50	1072000000
WAD 4 WS	4 mm	50	1072100000


DEK 5/5 / WS 8/5	Test plug and socket, see „W-Series Accessories“ section Note the 2.5 mm <sup>2</sup> max. when using the WQB.
------------------	---


## WDK 2.5

2.5 mm<sup>2</sup>

### Screwable cross-connection



5.1 x 69 x 63	
<b>32 / 4</b>	
<b>0.05...4</b>	

IEC 60947-7-1				Ex e II  II 2 G D	
IEC	UL	CSA	EN 60079-7		
400	300	300	275		
24	20	10	21		
2.5	AWG 30...12	AWG 26...12	2.5		
6 / 3					
A3 / V-0					
KEMA 98ATEX1687 U					
Rated connection					
0.5...4 / 1.5...4					
0.5...4 / 0.5...2.5					
0.4...0.6 Nm (M 2.5)					
10 / 0.6 x 3.5 mm					
0.5...1.5					
0.5...1.5 / 0.5...1.5					
2.5 mm <sup>2</sup> conductor with wire end ferrule plus plastic collar only with collar optimised for diameter (order No. 1333100000, 500 pcs)					

Type	Qty	Order No.
WDK 2.5	100	1021500000
WDK 2.5 BL	100	1021580000
For colours available see section „W-series accessories“, „Specific functions“		

Type	current	Qty	Order No.
WQV 2.5/2	32 A	50	1053660000
WQV 2.5/3	32 A	50	1053760000
WQV 2.5/4	32 A	50	1053860000
WQV 2.5/10	32 A	20	1054460000
Width			
WAP WDK2.5	1.5 mm	20	1059100000
WAP WDK2.5 BL	1.5 mm	20	1059180000
WTW EN	3 mm	20	1058800000
WEW 35/2	8 mm	100	1061200000
WAD 4 GE BED	4 mm	50	1072000000
WAD 4 WS	4 mm	50	1072100000

DEK 5/5 / WS 8/5	Test plug and socket, see „W-Series Accessories“ section Note the 2.5 mm <sup>2</sup> max. when using the WQB.
------------------	---


**WDK 2.5 V**

**2.5 mm<sup>2</sup>**

Both levels at one potential



5.1 x 69.5 x 63  
**32 / 4**  
**0.05...4**



IEC 60947-7-1 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
400	300	300	275
24	20	10	21
2.5	AWG 30...12	AWG 26...12	2.5
6 / 3			
A3 / V-0			

KEMA 98ATEX1687 U

**Rated connection**

0.5...4 / 1.5...4  
0.5...4 / 0.5...2.5  
0.4...0.6 Nm (M 2.5)  
10 / 0.6 x 3.5 mm

0.5...1.5  
0.5...1.5 / 0.5...1.5

2.5 mm<sup>2</sup> conductor with wire end ferrule plus plastic collar only with collar optimised for diameter (order No. 1333100000, 500 pcs)

Type	Qty	Order No.
WDK 2.5V	100	<b>1022300000</b>
WDK 2.5V BL	100	<b>1022380000</b>

For colours available see section W-series accessories „Specific functions“

Type	Qty	Order No.
<b>current</b>		
WQV 2.5/2	32 A 50	<b>1053660000</b>
WQV 2.5/3	32 A 50	<b>1053760000</b>
WQV 2.5/4	32 A 50	<b>1053860000</b>
WQV 2.5/10	32 A 20	<b>1054460000</b>
<b>Width</b>		
WAP WDK2.5	1.5 mm 20	<b>1059100000</b>
WAP WDK2.5 BL	1.5 mm 20	<b>1059180000</b>
WTW EN	3 mm 20	<b>1058800000</b>
<b>Width</b>		
WEW 35/2	8 mm 100	<b>1061200000</b>
WAD 4 GE BED	4 mm 50	<b>1072000000</b>
WAD 4 WS	4 mm 50	<b>1072100000</b>

DEK 5/5 / WS 8/5

Test plug and socket, see „W-Series Accessories“ section  
Note the 2.5 mm<sup>2</sup> max. when using the WQB.


**WDK 2.5 DU-PE**

**2.5 mm<sup>2</sup>**

Lower level earthed on terminal rail



5.1 x 69.5 x 63  
**32 / 4**  
**0.05...4**



IEC 60947-7-1 (-7-2) Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
400	300	300	275
24	20	10	21
2.5	AWG 30...12	AWG 26...12	2.5
6 / 3			
A3 / V-0			

KEMA 98ATEX1687 U

**Rated connection**

0.5...4 / 1.5...4  
0.5...4 / 0.5...2.5  
0.4...0.6 Nm (M 2.5)  
10 / 0.6 x 3.5 mm

0.5...1.5  
0.5...1.5 / 0.5...1.5

2.5 mm<sup>2</sup> conductor with wire end ferrule plus plastic collar only with collar optimised for diameter (order No. 1333100000, 500 pcs)

Type	Qty	Order No.
WDK 2.5DU-PE	100	<b>1036400000</b>

Type	Qty	Order No.
<b>current</b>		
WQV 2.5/2	32 A 50	<b>1053660000</b>
WQV 2.5/3	32 A 50	<b>1053760000</b>
WQV 2.5/4	32 A 50	<b>1053860000</b>
WQV 2.5/10	32 A 20	<b>1054460000</b>
<b>Width</b>		
WAP WDK2.5	1.5 mm 20	<b>1059100000</b>
WAP WDK2.5 BL	1.5 mm 20	<b>1059180000</b>
WTW EN	3 mm 20	<b>1058800000</b>
<b>Width</b>		
WEW 35/2	8 mm 100	<b>1061200000</b>
WAD 4 GE BED	4 mm 50	<b>1072000000</b>
WAD 4 WS	4 mm 50	<b>1072100000</b>

DEK 5/5 / WS 8/5

Test plug and socket, see section „W-Series accessories“  
Note the 2.5 mm<sup>2</sup> max. when using the WQB.


**WDK 2.5 / 800 V**

**2.5 mm<sup>2</sup>**

Rated voltage 800 V



6.1 x 69 x 63  
**32 / 4**  
**0.05...4**



IEC 60947-7-1 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
800			440
24			24
2.5			2.5
8 / 3			
A3 / V-0			

KEMA 98ATEX1685 U

**Rated connection**

0.5...4 / 1.5...4  
0.5...4 / 0.5...2.5  
0.4...0.6 Nm (M 2.5)  
10 / 0.6 x 3.5 mm

0.5...1.5  
0.5...1.5 / 0.5...1.5

Type	Qty	Order No.
WDK 2.5/800V	100	<b>1029100000</b>

Type	Qty	Order No.
<b>current</b>		
Q 2 AKZ4SS	20 A 50	<b>0369000000</b>
Q 3 AKZ4SS	20 A 50	<b>0369100000</b>
Q 4 AKZ4SS	20 A 50	<b>0369200000</b>
Q 10 AKZ4SS	20 A 20	<b>0369300000</b>
<b>Width</b>		
WAP WDK2.5	1.5 mm 20	<b>1059100000</b>
WAP WDK2.5 BL	1.5 mm 20	<b>1059180000</b>
WAP 16+35 WTW 2.5-10	1.5 mm 20	<b>1050100000</b>
<b>Width</b>		
WEW 35/2	8 mm 100	<b>1061200000</b>
WAD 4 GE BED	4 mm 50	<b>1072000000</b>
WAD 4 WS	4 mm 50	<b>1072100000</b>

DEK 5/6 / WS 8/5

Test plug and socket, see „W-Series Accessories“ section  
Note the 2.5 mm<sup>2</sup> max. when using the WQB.

## Double level terminals

Identical profiles from 2.5 to 10 mm<sup>2</sup> with uniform end and partition plates. An unsurpassed combination of many advantages!

Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.

In hazardous area applications, the installation instructions and the rated data specifications for accessories given in the technical appendix must be followed.

Width/Length/height with TS35x7.5	mm
max. current / max. cond. cross-section	A/mm <sup>2</sup>
Max. clamping range	mm <sup>2</sup>




### Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm <sup>2</sup>
Rated impulse voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	
Clamped conductors (H05V/H07V)	
solid / stranded	mm <sup>2</sup>
flexible / Stranded wire with end ferrules	mm <sup>2</sup>
Tightening torque range (clamping screw)	
Stripping length / Blade size	mm/-
2 conductors with same cross-section (H05V/H07V)	
solid / stranded	mm <sup>2</sup>
flexible / Stranded wire with end ferrules	mm <sup>2</sup>
Note	

### Ordering data

Version	
	Dark beige Wemid
	Blue Wemid
Note	

### Accessories


Pluggable cross-connection	
	2-pole
	3-pole
	4-pole
	10-pole
	20-/24-pole
Screwable cross-connection	
	2-pole
	3-pole
	4-pole
	10-pole
End plate / partition	
	Dark beige Wemid
	Blue Wemid
	Dark beige Wemid
End bracket	
	Dark beige Wemid
Cover	
	With lightning flash symbol
	blank
Marking systems	
	(see assortment in catalogue 7)
	Marking tags
For detailed information on other accessories and applications, refer to the „Accessories“ section	



## WDK 2.5N

2.5 mm<sup>2</sup>

Plug-in cross-connection  
Compact design



5.1 x 60.7 x 62.5	
<b>28 / 4</b>	
<b>0.05...4</b>	

IEC 60947-7-1				Ex e ll  II 2 G D			
IEC	UL	CSA	EN 60079-7	IEC	UL	CSA	EN 60079-7
800	600	300	550	800	600	300	550
24	20	20	21	24	20	20	21
2.5	AWG 30...12	AWG 26...12	2.5	2.5	AWG 30...12	AWG 26...12	2.5
				8 / 3			
				A3 / V-0			
				KEMA 00ATEX2061 U			
Rated connection							
0.5...4 / 1.5...4							
0.5...4 / 0.5...2.5							
0.4...0.6 Nm (M 2.5)							
8 / 0.6 x 3.5 mm							
0.5...1.5							
0.5...1.5 / 0.5...1.5							
When using the cross-connection ZQV 2.5N, the rated voltage is reduced to 400 V.							

Type	Qty	Order No.
WDK 2.5N	100	1041600000
WDK 2.5N BL	100	1041680000


Type	current	Qty	Order No.
ZQV 2.5N/2 GE	24 A	60	1693800000
ZQV 2.5N/3 GE	24 A	60	1693810000
ZQV 2.5N/4 GE	24 A	60	1693820000
ZQV 2.5N/10 GE	24 A	20	1693880000
ZQV 2.5N/20 GE	24 A	20	1909000000
Width			
WAP WDK2.5/4 N	1.5 mm	20	1084000000
WAP WDK2.5/4 N BL	1.5 mm	20	1084080000
WTW EN	3 mm	20	1058800000
Width			
WEW 35/2	8 mm	100	1061200000
DEK 5/5 / WS 8/5			



## WDK 2.5N V

2.5 mm<sup>2</sup>

Both levels at one potential  
Compact design



5.1 x 60.7 x 62.5	
<b>28 / 4</b>	
<b>0.05...4</b>	

IEC 60947-7-1				Ex e ll  II 2 G D			
IEC	UL	CSA	EN 60079-7	IEC	UL	CSA	EN 60079-7
800	600	300	550	800	600	300	550
24	20	20	21	24	20	20	21
2.5	AWG 30...12	AWG 26...12	2.5	2.5	AWG 30...12	AWG 26...12	2.5
				8 / 3			
				A3 / V-0			
				KEMA 00ATEX2061 U			
Rated connection							
0.5...4 / 1.5...4							
0.5...4 / 0.5...2.5							
0.4...0.6 Nm (M 2.5)							
8 / 0.6 x 3.5 mm							
0.5...1.5							
0.5...1.5 / 0.5...1.5							
When using the cross-connection ZQV, the rated voltage is reduced to 400 V.							

Type	Qty	Order No.
WDK 2.5N V	100	1041610000


Type	current	Qty	Order No.
ZQV 2.5N/2 GE	24 A	60	1693800000
ZQV 2.5N/3 GE	24 A	60	1693810000
ZQV 2.5N/4 GE	24 A	60	1693820000
ZQV 2.5N/10 GE	24 A	20	1693880000
ZQV 2.5N/20 GE	24 A	20	1909000000
Width			
WAP WDK2.5/4 N	1.5 mm	20	1084000000
WAP WDK2.5/4 N BL	1.5 mm	20	1084080000
WTW EN	3 mm	20	1058800000
Width			
WEW 35/2	8 mm	100	1061200000
DEK 5/5 / WS 8/5			

**WDK 2.5N DU-PE** 2.5 mm<sup>2</sup>

Lower level earthed on terminal rail  
Compact design



5.1 x 60.7 x 62.5  
28 / 4  
0.05...4



IEC 60947-7-1 (-7-2) Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	300	550
24	20	20	21
2.5	AWG 30...12	AWG 26...12	2.5
8 / 3			
A3 / V-0			

KEMA 00ATEX2061 U

Rated connection	
0.5...4 / 1.5...4	
0.5...4 / 0.5...2.5	
0.4...0.6 Nm (M 2.5)	
8 / 0.6 x 3.5 mm	
0.5...1.5	
0.5...1.5 / 0.5...1.5	
When using the cross-connection ZQV, the rated voltage is reduced to 400 V.	

Type	Qty	Order No.
WDK 2.5N DU-PE	100	1041650000

Type	current	Qty	Order No.
ZQV 2.5N/2 GE	24 A	60	1693800000
ZQV 2.5N/3 GE	24 A	60	1693810000
ZQV 2.5N/4 GE	24 A	60	1693820000
ZQV 2.5N/10 GE	24 A	20	1693880000
ZQV 2.5N/20 GE	24 A	20	1909000000

Width			
WAP WDK2.5/4 N	1.5 mm	20	1084000000
WAP WDK2.5/4 N BL	1.5 mm	20	1084080000
WTW EN	3 mm	20	1058800000
WEW 35/2	8 mm	100	1061200000


DEK 5/5 / WS 8/5

**WDK 4N** 4 mm<sup>2</sup>

Plug-in cross-connection  
Compact design



6.1 x 60 x 64.1  
35 / 6  
0.13...6



IEC 60947-7-1 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	300	550
32	35	30	28
4	AWG 26...10	AWG 26...10	4
8 / 3			
A4 / V-0			

KEMA 00ATEX2061 U

Rated connection	
0.5...6 / 1.5...6	
0.5...4 / 0.5...4	
0.5...1.0 Nm (M 3)	
8 / 0.6 x 3.5 mm	
0.5...1.5	
0.5...1.5 / 0.5...1.5	
Rated voltage: 400V when using ZQV cross-connection 2 wire H07V-U1.5, tighten with 0.6 Nm.	

Type	Qty	Order No.
WDK 4N	100	1041900000
WDK 4N BL	100	1041980000

Type	current	Qty	Order No.
ZQV 4N/2 GE	32 A	60	1758250000
ZQV 4N/3 GE	32 A	60	1762630000
ZQV 4N/4 GE	32 A	60	1762620000
ZQV 4N/10 GE	32 A	20	1758260000
ZQV 4N/20 GE	32 A	20	1909020000

Width			
WAP WDK2.5/4 N	1.5 mm	20	1084000000
WAP WDK2.5/4 N BL	1.5 mm	20	1084080000
WTW EN	3 mm	20	1058800000
WEW 35/2	8 mm	100	1061200000

DEK 5/6 / WS 8/5


Test plug and socket, see „W-Series Accessories“ section  
Note the 2.5 mm<sup>2</sup> max. when using the WQB.

**WDK 4N V** 4 mm<sup>2</sup>

Both levels at one potential  
Compact design



6.1 x 60.7 x 64.1  
35 / 6  
0.13...6



IEC 60947-7-1 Ex e II II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	300	550
32	35	30	28
4	AWG 26...10	AWG 26...10	4
8 / 3			
A4 / V-0			

KEMA 00ATEX2061 U

Rated connection	
0.5...6 / 1.5...6	
0.5...4 / 0.5...4	
0.5...1.0 Nm (M 3)	
8 / 0.6 x 3.5 mm	
0.5...1.5	
0.5...1.5 / 0.5...1.5	
Rated voltage: 400V when using ZQV cross-connection 2 wire H07V-U1.5, tighten with 0.6 Nm.	

Type	Qty	Order No.
WDK 4N V	100	1041910000

Type	current	Qty	Order No.
ZQV 4N/2 GE	32 A	60	1758250000
ZQV 4N/3 GE	32 A	60	1762630000
ZQV 4N/4 GE	32 A	60	1762620000
ZQV 4N/10 GE	32 A	20	1758260000
ZQV 4N/20 GE	32 A	20	1909020000

Width			
WAP WDK2.5/4 N	1.5 mm	20	1084000000
WAP WDK2.5/4 N BL	1.5 mm	20	1084080000
WTW EN	3 mm	20	1058800000
WEW 35/2	8 mm	100	1061200000

DEK 5/6 / WS 8/5

Test plug and socket, see „W-Series Accessories“ section  
Note the 2.5 mm<sup>2</sup> max. when using the WQB.

## Double level terminals

Identical profiles from 2.5 to 10 mm<sup>2</sup> with uniform end and partition plates. An unsurpassed combination of many advantages!

Their small size compared to the respective rated cross-section makes the modular terminals with the compact design very popular.

In hazardous area applications, the installation instructions and the rated data specifications for accessories given in the technical appendix must be followed.

Width/Length/height with TS35x7.5	mm
max. current / max. cond. cross-section	A/mm <sup>2</sup>
Max. clamping range	mm <sup>2</sup>

### Technical data

Rated data	
Rated voltage	V
Rated current	A
Rated cross-section	mm <sup>2</sup>
Rated impulse voltage / Pollution severity	kV/-
Gauge to IEC 60947-1 / UL94 Flammability class	
Approvals	

#### Clamped conductors (H05V/H07V)

solid / stranded	mm <sup>2</sup>
flexible / Stranded wire with end ferrules	mm <sup>2</sup>
Tightening torque range (clamping screw)	
Stripping length / Blade size	mm/-

#### 2 conductors with same cross-section (H05V/H07V)

solid / stranded	mm <sup>2</sup>
flexible / Stranded wire with end ferrules	mm <sup>2</sup>

#### Note

### Ordering data

Version	
	Dark beige Wemid
	Blue Wemid

#### Note

### Accessories

#### Pluggable cross-connection



2-pole	
3-pole	
4-pole	
10-pole	
20-/24-pole	

#### Screwable cross-connection



2-pole	
3-pole	
4-pole	
10-pole	

#### End plate / partition

Dark beige Wemid	
Blue Wemid	
Dark beige Wemid	

#### End bracket

Dark beige Wemid	
------------------	--

#### Cover



With lightning flash symbol	
blank	

#### Marking systems

(see assortment in catalogue 7)

Marking tags

**For detailed information on other accessories and applications, refer to the „Accessories“ section**

## WDK 4N DU-PE

4 mm<sup>2</sup>

Lower level earthed on terminal rail


Compact design



6.1 x 60.7 x 64.1

35 / 6

0.13...6



IEC 60947-7-1 (-7-2)

Ex e ll II 2 G D

IEC	UL	CSA	EN 60079-7
800	600	300	550
32	35	30	28
4	AWG 26...10	AWG 26...10	4
8 / 3			
A4 / V-0			

KEMA 00ATEX2061 U

#### Rated connection

0.5...6 / 1.5...6
0.5...4 / 0.5...4
0.5...1.0 Nm (M 3)
8 / 0.6 x 3.5 mm
0.5...1.5
0.5...1.5 / 0.5...1.5

Rated voltage is 400 V when using the ZQV cross-connector.  
It is prohibited to connect two conductors via the PE connection!

Type	Qty	Order No.
WDK 4N DU-PE	100	1041950000

Type	current	Qty	Order No.
ZQV 4N/2 GE	32 A	60	1758250000
ZQV 4N/3 GE	32 A	60	1762630000
ZQV 4N/4 GE	32 A	60	1762620000
ZQV 4N/10 GE	32 A	20	1758260000
ZQV 4N/20 GE	32 A	20	1909020000

Width			
WAP WDK2.5/4 N	1.5 mm	20	1084000000
WAP WDK2.5/4 N BL	1.5 mm	20	1084080000
WTW EN	3 mm	20	1058800000
WEW 35/2	8 mm	100	1061200000

DEK 5/6 / WS 8/5

Test plug and socket, see „W-Series Accessories“ section  
Note the 2.5 mm<sup>2</sup> max. when using the WQB.